

MORBARK® BEEVER™ M12R TRACK



BENEFITS

- With its power and easily transportable design, this compact and economical chipper is the ideal unit for right-of-way and utility line clearing, highway clean-ups, residential tree services, rental yards and municipalities.
- The patented chambered air impeller system increases chip throwing velocity and reduces dust and material blowback out the infeed to pack more into the chip truck.
- The direct driven dual feed wheel system with serrated teeth and knife bar combination and end cap ripper teeth allow positive material feeding and reduced material wrapping around the feed wheel shaft for increased feeding efficiency.
- Like all Morbark equipment, the M12R is a long-lasting, durable machine backed by a world-class parts and service support team.



Infeed Opening

The 60" wide x 31" high chute opening and 15" wide x 12" high throat opening allows for easy feeding of branchy material and reduced saw labor.



Track Undercarriage

Take the chipper to the material with a two-speed, 72" long x 9" wide, turf-friendly rubber track undercarriage and 4.94 PSI ground pressure.



Hydra-Lift System

The powerful Hydra-Lift™ dual feed wheel compression system with spring-assisted down pressure generates more than 3,300 lb./ft. of combined material pulling force.



360° Swivel Discharge

360° swivel discharge with chip deflectors puts chips right where they're needed.

SPECIFICATIONS

SPECIFICATIONS MAY VARY WITH EQUIPMENT OPTIONS 5/14/12

General

Chipping capacity 12"
 Height 8'
 Width 6'3"
 Length 13'9"
 Gross weight 6,414 lbs.
 Infeed opening 60" wide x 31" high
 Throat opening 15" wide x 12" high
 Drum 14 1/4" wide x 21" diameter
 Engine CAT or Kubota
 Horsepower 84–114 HP
 Fuel capacity 24 1/2 gallons
 Hydraulic capacity 17 1/2 gallons
 Frame 2" x 4" tubular

Equipment Highlights

Wireless Remote Control operation with tethered back-up system controls the track functions, feed functions, yoke functions and throttle functions with emergency engine stop
 Dual horizontal feed wheel compression system with hydraulic lift assist, spring assisted down pressure and manually applied hydraulic down pressure at the valve handle
 Reversing automatic feed system
 Enclosed engine with gauge panel, radiator fines screen and slide rails for belt adjustment
 Fuel tank sight gauge, drain plug and shut-off valve
 Hydraulic tank shut-off valve, drain plug and clean-out cover

Additional Features

Live hydraulics; ball valve, pump, motor, control valve and variable speed flow control
 Steel guard enclosing valve bank and automatic feed system components
 Morthane Paint System: A chemically cured, electrostatically applied urethane coating with high-gloss finish, built-in UV protection, chip and chemical resistance and corrosion protection

Options

Custom paint and logo packages
 Knife saver tool
 Engine stop on infeed
 Material pushing tool
 Discharge cleanout door on bottom
 Rubber infeed curtain
 Spanish and English safety decals



MORBARK®
 BUILDING EQUIPMENT THAT CREATES OPPORTUNITIES

800.831.0042
 989.866.2381
www.morbark.com

PO Box 1000
 8507 S. Winn Rd.
 Winn, MI 48896