

# MORBARK® BEEVER™ M20R W/LOADER

## BENEFITS

- Powerful Mor-Lift Model 150M Hydraulic Knuckleboom Loader with exclusive operator's seat and platform allows operators to see more, reach farther and pick-up more material.
- Increases efficiency by reducing cost and labor by eliminating the need for additional auxiliary equipment needed to feed the chipper.
- Increased versatility by having three chippers in one when equipped with an optional wireless remote control. When the loader is cradled, the machine can be hand fed, or fed by an auxiliary piece of equipment (not applicable when ordered with Infeed Deck) with the flip of a switch.
- Ideal unit for: Entry-level biomass production, lot and land clearing contractors, contractors and large tree services. Also available in Trailer, Infeed Deck and Track configurations



### OPERATOR SEAT

Morbark's exclusive operator's seat and platform provides a 270° birds eye view of the chipping operation



### LOADER

Mor-Lift Model 150M Knuckleboom Loader provides a 14' extended boom reach and 2680lb lift at a 10' reach



### GRAPPLE

Model 649 continuous rotation, by-pass grapple with 6" closed tine diameter and 49 9/16" tine opening



### TURNTABLE/PEDESTAL

Pedestal mount features a heavy-duty, 23" diameter, turntable bearing and 59.9ci turn motor

## SPECIFICATIONS

Note: Specifications may vary with equipment options

06092010

### GENERAL

Chipping capacity .....20"  
 Length ..... 21'4"  
 Height ..... 11'3"  
 Width .....7'8"  
 Gross weight ..... 17,500 lbs.  
 Suspension ..... (2) 10,000 lb. torsion  
 Infeed opening..... 65" wide x 39" high  
 Throat opening .....28" wide x 20 3/8" high  
 Drum .....28 1/2" wide x 37 3/8" diameter  
 Engine..... CAT, Cummins or John Deere  
 Horsepower..... 325-350 HP  
 Fuel capacity ..... 65 gallons  
 Hydraulic oil capacity..... 43 gallons  
 Frame .....2" x 8" tubular steel  
 Tires ..... (4) 235/75R x 17.5"  
 Hitch.....3" lunet

### EQUIPMENT HIGHLIGHTS

Mor-Lift Model 150M Hydraulic Knuckleboom Loader Package with 14' extended boom reach and 1.2 ton pick capacity at 10' reach  
 Model 649, continuous rotation by-pass grapple with 6" closed tine diameter, 49" tine opening and 3" welded cylinder  
 Pedestal mount features a heavy-duty 23" diameter turntable bearing with powerful 59.9ci turntable motor  
 Heavy-duty 3" welded main boom cylinder and 3.5" welded main boom cylinder  
 Hydraulic front stabilizer and hydraulic dual rear stabilizers  
 Integrated front load carriage for ease of loader transport  
 AR-400 Wear resistant steel in critical wear areas  
 Morthane Paint System: A chemically cured, electrostatically applied urethane coating with high gloss finish, built in UV protection, chip and chemical resistance and corrosion protection

### ADDITIONAL FEATURES

Fixed drawbar length with optional bolt-on extensions  
 Chipper belt inspection cover  
 Hydraulic tank inspection cover  
 Steel guard enclosing valve bank and auto-feed components  
 360° Hydraulic swivel discharge with adjustable chip deflector

### OPTIONS

Ground mounted operator's controls  
 Winch package  
 5' Rigid infeed deck  
 Custom paint and logo packages  
 Engine E-stop  
 Wireless remote control



800-831-0042 989-866-2381  
[www.morbark.com](http://www.morbark.com)